




TOP VIEW



SIDE VIEW



BACK VIEW



BACK VIEW A

**General Information**

Product Code	AIS-WHT-101153
Brand	Essco
Colour	White
Type	Wall Mounted Bidet
Material	Ceramic-Vitreous China (VC)

**Product Specification**

Product Dimension	350x510x360 mm
Bowl Inner Dimension	280x345 mm
Product Net Weight	17 Kg
Product Gross Weight	19.0 Kg
Packaging Dimension	365x355x515 mm
Outlet	Vertical

Tap Hole And Outlet Hole Dimension	Tap hole dia. $\varnothing 35 \pm 2$ mm
	Internal diameter of outlet hole dia. $\varnothing 45 \pm 3$ mm
	Horizontal distance between the center line of the tap hole and the center line of the waste outlet hole $\leq 160$ mm

Product Features	Wall hung rectangular-shape bidet Bidet With Overflow Hole And Tap Hole Anti Bacterial Glaze on Ceramic Smooth Glaze Surface Material - Vitreous China (VC)
------------------	---

**ACCESSORIES INCLUDED**

Overflow hole cap	ZPS-WHT-9012B
-------------------	---------------

**ACCESSORIES RECOMMENDATION**

Rack bolt	ZPS-SNS-RB01,ZPS-MST-RB02,ZPS-MST-RB07
-----------	--

**CARE AND CLEANING GUIDELINES**

- Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- The product is heavy and it is recommended that two persons hold it while it is being fixed.
- Carefully inspect the new product for damage before installation.
- Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- Risk of external leakage. Do not lift or rock the bowl after placement.
- Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- Do not allow cleaners to sit or soak on the product.
- Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

**QUALITY MANAGEMENT SYSTEM - ISO 9001**



DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance  $\pm 5$  MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice.

# For Installation Refer Actual Product